



Star LED Bulkhead with easy installation ,this light adopts die-cast aluminum body and 94-v0 fire-rated PC cover ,color changeable function make this bulkhead can change color temperature from warm white to cool white., size 300mmX100mm, this bulkhead ideal Applications that require continuous light good to provide high bright lighting to stairway, lobby, reception, corridors etc.

Description

Housing - Die-cast Aluminum

Diffuser - 94-v0 Fire-rated PC diffuser

Reflector - Aluminium Reflector

Color Available - White, Black & Dark-Gray

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -10C° ~ +50C°

IP Rating - 65


IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL343518	18W	LED	2160lm	A300 X B100mm
LP-ODL343524	24W	LED	2880lm	A300 X B100mm
LP-ODL343536	36W	LED	4320lm	A300 X B100mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS STAR

WALL SURFACE LIGHT

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk