



Sunny LED Fixture for illuminating common or outdoor areas near homes, is suitable for indoor and outdoor areas, with ceiling or wall installation where more intense and diffused lighting is required. It is particularly suited for lighting stairs, building entrance areas, corridors in shopping malls, shops, hotels & restaurants. Possibility of customising it by changing the type of light source. The wide range of Mazda LED light sources with LED and CFL sources or even to transform it into emergency lighting.

Description

Housing - Vandal Resistant & V2 Self Extinguishing Polycarbonate
UV Stabilized

Diffuser - Anti Glare with UV Polycarbonate

Reflector - Aluminium Reflector

Color Available - White

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC110~240V

Working Temperature - -10C° ~ +50C°


IP Rating - 65

Item Code	Power	Lamp	Lumen	Dimensions
LP-ODL451518	18W	LED	2160lm	A300 X B221 X C40mm
LP-ODL451525	25W	LED	3000lm	A350 X B221 X C40mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS SUNNY

CEILING SURFACE LIGHT

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk