



OUTDOOR LIGHTS TAM

BOLLARD LIGHT

Kelvin

2700K – warm white, similar to incandescent bulb
3000K – soft white, similar to halogen bulb
4000K – bright white, similar to fluorescent lighting
5000K – daylight, very bright & similar to sunlight
6000K – cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk



Tam LED Light are a great design choice for gardens, walkways, and around the buildings, available with little differences in the top shape to satisfy the details lovers. The light source is an LED high efficiency system, which ensures high performances while saving energy. All the items have features like easy installation, very low maintenance needs and full safety for electrical systems and people.

Description

Housing - Body is Die-casting Aluminum Cover, Extruded Aluminum Pole. Finishing Surface Anti-ageing Electrostatic Spray Processing.

Diffuser - PMMA

Reflector - Aluminum Reflector

Color Available - White, Black & Grey

Lifespan - >50,000 Hours (L90 B10)


Voltage - AC220-240V

IP Rating - 66

IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-BL333012-H80	12W	LED	1440lm	A125 X B125 X C800mm
LP-BL333015-H80	15W	LED	1800lm	A125 X B125 X C800mm

Photometrics



Technical Drawing

