



A versatile street luminaire that balances cost, output, and longevity. Precision lenses shape the beam for local streets, collectors, and pathways. Tool-free latching and a hinged gear tray make servicing straightforward.

Description

Housing - Die Cast Aluminum, Extruded Aluminum Pole

Diffuser - Clear PC

Color Available - Black

Lifespan - >50,000 Hours (L70 B10)

Voltage - AC220~240V

Working Temperature - -20° ~ +65°C

IP Rating - 65

IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR318108	08W	LED	-----	AØ180 X B600 mm
LP-STR318116	16W	LED	1271lm	AØ250 X B1220 mm
LP-STR318125	25W	LED	-----	AØ180 X B600 mm
LP-STR318140	40W	LED	3153lm	AØ250 X B1220 mm

OUTDOOR LIGHTS WESMINSTER

DECORATIVE POLE

Kelvin

2700K - warm white, similar to incandescent bulb

3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk







Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Technical Drawing




Photometrics




	H(m)	Eavg(lx)	Emax(lx)	D(m)
1	101.5	292.1	2.92	
2	25.4	73.0	5.84	
3	11.3	32.5	8.77	
4	6.3	18.3	11.69	
5	4.1	11.7	14.62	

16W LED 1271lm
Opal PC
Class I, IP65



	H(m)	Eavg(lx)	Emax(lx)	D(m)
1	89.1	111.9	2.00	
2	22.3	28.0	4.00	
3	9.9	12.4	6.00	
4	5.6	7.0	8.00	
5	3.6	4.5	10.00	

MTC 2835 LED 40W 3153lm
Opal PC
Class I, IP65



	H(m)	Eavg(lx)	Emax(lx)	D(m)
1	37.4	43.8	2.00	
2	9.4	11.0	4.00	
3	4.2	4.9	6.00	
4	2.3	2.7	8.00	
5	0.0	1.8	10.00	

8W LED
Opal PC
Class I, IP65