


OUTDOOR LIGHTS WINCHESTER

STREET LIGHTS

Kelvin

- 2700K – warm white, similar to incandescent bulb
- 3000K – soft white, similar to halogen bulb
- 4000K – bright white, similar to fluorescent lighting
- 5000K – daylight, very bright & similar to sunlight
- 6000K – cool white, blue tinted, like a monitor

Beam Angle



A roadway fixture with attention to glare control and backlight reduction. House-side shields are available to protect adjacent residences. Controls include step-dimming, motion activation, and central management compatibility.

LED CHIP



LED DRIVER



Description

Housing - Die-Casting Aluminum Body

Diffuser - Clear Glass

Color Available - Black & Grey

Lifespan - >50,000 Hours (L70 B10)

Voltage - AC220-240V

Working Temperature - -20° ~ +65°C

IP Rating - 65

IK - 10

Item Code	Power	Lamp	Lumen	Dimensions
LP-STR32275	75W	LED	-----	A526 X B236 X C86 mm
LP-STR322120	120W	LED	-----	A584 X B253 X C86 mm
LP-STR322200	200W	LED	-----	A703 X B295 X C91 mm
LP-STR322300	300W	LED	-----	A769 X B346 X C91 mm



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk

Photometrics

Technical Drawing

