



The Radiant LED flood lights offers the widest variety of mounting options available. For LED flood lights with fashionable appearance, scientific light distribution, efficiency and ECO performance. This is fully visible, and the direction of the light beam can be adjusted. The best economic fit in doorway, yard, garden, landscape, and piers, etc. can be illuminated.

Description

Housing - Body in Aluminum Die-cast Powder Coating

Diffuser - Clear Froasted, Tempered Glass

Reflector - Aluminum Reflector

Color Available - Bronze Metallic, Black, White

Lifespan - > 100,000 Hours (L90 B50)

Voltage - AC220~240V


Working Temperature - -40C° ~ +55C°

IP Rating - 67


IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-SL172210	10W	LED	1200lm	A90 X B90 X C97mm
LP-SL172215	15W	LED	1800lm	A90 X B90 X C97mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS RADIANT

FLOOD LIGHTS

Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk