



Sharp II LED Flood Light is a cost-effective solution, with full range of wattage and optional light distribution, Sharp II is available for multiple applications. Multiple light distributions for different applications even for stadium and billboard. It can also be used as street light with slip fitter mounting accessory.

Description

Housing - Die cast Housing with black powder coat

Diffuser - Tempered Glass

Reflector - Aluminum Reflector

Color Available - All RAL Color

Lifespan - >50,000 Hours (L90 B10)

Voltage - AC220~240V


Working Temperature - -30C° ~ +60C°

IP Rating - 66


IK - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-FL307080	80W	LED	8000lm	A287xB236xC160mm
LP-FL3070100	100W	LED	10000lm	A287xB236xC160mm
LP-FL3070120	120W	LED	12000lm	A287xB236xC160mm
LP-FL3070150	150W	LED	15000lm	A287xB236xC160mm

Photometrics



Technical Drawing



OUTDOOR LIGHTS SHARP II

FLOOD LIGHTS

Kelvin

2700K - warm white, similar to incandescent bulb


3000K - soft white, similar to halogen bulb

4000K - bright white, similar to fluorescent lighting

5000K - daylight, very bright & similar to sunlight

6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER



This text is a standard disclaimer often found in product catalogs, brochures, or specification sheets. It informs customers that the company may update product specifications or materials at its discretion to improve the product, without prior notice, provided these changes do not affect its functionality. It also clarifies that the most up-to-date information is available on their website, which takes precedence over other sources.

If this is for inclusion in your materials, you might consider customizing it to match your company's policies or branding. Let me know if you'd like assistance tailoring it!



www.lightplus.uk