




Kelvin

- 2700K - warm white, similar to incandescent bulb
- 3000K - soft white, similar to halogen bulb
- 4000K - bright white, similar to fluorescent lighting
- 5000K - daylight, very bright & similar to sunlight
- 6000K - cool white, blue tinted, like a monitor

Beam Angle



LED CHIP



LED DRIVER




Marina is a compact linear luminaire with six COB LEDs behind clear tempered glass in an extruded aluminium body, IP68 sealed and IK08 rated. Sections link end to end and hinge to follow curves and corners, with a bracket for surface fixing. Available in white, RGB and RGBW, with Triac, 0/1-10V, DALI and DMX control.

Description

- Housing** - Extruded Aluminum
- Reflector** - Aluminum
- Diffuser** - Clear Tempered Glass
- Beam Angle** - 20° / 30° / 60° / 80°
- CRI** - >90
- Color Available** - 3000K, 4000K, 6000K, RGB, RGBW
- Finish** - Black, Gray
- Color Consistency** - SDCM<3
- Efficacy** - 120 lm/W
- Power Factor** - 0.9
- Lifespan** - >50,000 Hours
- Voltage** - AC220V / DC24V 50/60Hz
- Dimming** - Triac, 0/1-10V, DALI, DMX
- Working Temperature** - -20C° ~ +60C°
- IP Rating** - 68
- IK** - 08

Item Code	Power	Lamp	Lumen	Dimensions
LP-UL604206	6 x 1W	COB LED	720lm	W42 x H75 x L166 mm
LP-UL604212	6 x 2W	COB LED	1440lm	W42 x H75 x L166 mm

Technical Drawing



Specifications, materials and finishes may be updated without prior notice as part of our continuous product improvement. Dimensions are nominal. Photometric data is provided for guidance; project-specific calculations should use the current files available on request. The latest version of this datasheet is published at www.lightplus.uk and takes precedence over any printed copy.

